

VOLDUE



Código Code	VO-120-2-CHS-LP *VO-120-2-CHS5050-LP	VO-180-3-CHS-LP *VO-180-3-CHS5050-LP	VO-240-4-CHS-LP *VO-240-4-CHS5050-LP
Modelo Model	VOLDUE -120-S / -CH5050	VOLDUE -180-S / -CH5050	VOLDUE -240-S / -CH5050
Potencia Power	120W	180W	240W
Tensión Tension	90-277 V~ (Cuenta con supresor de picos 10 Kv)	90-277 V~ (Cuenta con supresor de picos 10 Kv)	90-277 V~ (Cuenta con supresor de picos 10 Kv)
Equivalencia Equivalence	400 W AM	400 W AM	400 W AM
Factor de potencia Power factor	0.95	0.95	0.95
Lúmenes por watt Lumens per watt	127 ± 5 lm/w / 163 lm/w	127 ± 5 lm/w / 163 lm/w	127 ± 5 lm/w / 163 lm/w
Flujo luminoso Luminous flux	14,500 LM / 19,560 LM	28,620 LM / 29,340 LM	30,480 LM / 39,120 LM
Ángulo de apertura Opening range	25°, 40°, 60°, 90°	25°, 40°, 60°, 90°	25°, 40°, 60°, 90°
Vida útil Life	100,000 hrs	100,000 hrs	100,000 hrs
Índice de reproducción cromática Color rendering index	>70		
Temperatura de color Color temperature	5000 K		
Dimensiones (mm) Dimensions (mm)	360*200*175mm	360*200*255mm	360*260*335mm
Peso (Kg) Weight	4.7 ± 0.3Kg	5.6 ± 0.3Kg	6.7 ± 0.3Kg

