

VOLDUE



Código Code

VO-300-5-CHS-LP
***VO-300-5-CHS5050-LP**

VO-360-6-CHS-LP
***VO-360-6-CHS5050-LP**

VO-420-7-CHS-LP
***VO-420-7-CHS5050-LP**

Modelo Model	VOLDUE -300-S / -CH5050	VOLDUE -360-S / -CH5050	VOLDUE -420-S / -CH5050
Potencia Power	300W	360W	420W
Tensión Tension	90-277 V~ (Cuenta con supresor de picos 10 Kv)	90-277 V~ (Cuenta con supresor de picos 10 Kv)	90-277 V~ (Cuenta con supresor de picos 10 Kv)
Equivalencia Equivalence	1,000 W AM	1,000 W AM	1,000 W AM
Factor de potencia Power factor	0.95	0.95	0.95
Lúmenes por watt Lumens per watt	127 ± 5 lm/w / 163 lm/w	127 ± 5 lm/w / 163 lm/w	127 ± 5 lm/w / 163 lm/w
Flujo luminoso Luminous flux	38,100 LM / 48,900 LM	45,720 LM / 58,680 LM	50,400 LM / 68,460 LM
Ángulo de apertura Opening range	25°, 40°, 60°, 90°	25°, 40°, 60°, 90°	25°, 40°, 60°, 90°
Vida útil Life	100,000 hrs	100,000 hrs	100,000 hrs
Índice de reproducción cromática Color rendering index	>70		
Temperatura de color Color temperature	5000 K		
Dimensiones (mm) Dimensions (mm)	360*260*415mm	360*360*495mm	360*360*575mm
Peso (Kg) Weight	8 ± 3Kg	9.4 ± 0.3Kg	11.9 ± 0.3Kg



eco-lighting
Iluminación sustentable